

Hydraulic Rubber Hose

EN 856 4SH



4层钢丝缠绕橡胶软管

FOUR WIRE SPIRAL REINFORCED HYDRAULIC RUBBER HOSE

- * **Application:** For delivery of petroleum base hydraulic fluids or water base liquids.
- * **Inner tube:** Seamless oil resistant synthetic rubber.
- * **Reinforcement:** 4 spirals of high tensile steel wire.
- * **Outer cover:** Oil, weather and abrasion resistant synthetic rubber.
- * **Temperature Range:** -40°C ~ +100°C (-40°F ~ +212°F)
- * **Fittings:** Crimped hose fittings 2 series with ferrule 00400 or 00401 series.
- * **Specifications:**

产品型号	规格 SIZE	内径 I.D	增强层外径 W.D	外径 O.D	工作压力 W.P		最小爆破压力 B.P		最小弯曲半径 Min Bend Radius	参考重量 Weight
Part Number	inch	mm	mm	mm	bar	psi	bar	psi	mm	g/m
P10-4SH	5/8"	16	24.2	27.4	420	6090	1680	24360	240	1225
P12-4SH	3/4"	19	28.1	32	420	6090	1680	24360	280	1500
P16-4SH	1"	25.4	35.2	37.5	380	5510	1520	22040	340	2065
P20-4SH	1 1/4"	31.8	41.9	45.5	350	5075	1400	20300	460	2425
P24-4SH	1 1/2"	38.1	48.8	53.5	290	4205	1160	16820	560	3235
P32-4SH	2"	50.8	63.2	67.1	250	3625	1000	14500	700	4460